

View Online at <https://aerobasegroup.com/nsn/5930-00-150-1078>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof and humidity resistant and salt spray resistant

**Overall Length:**

2.554 inches

**Overall Height:**

1.938 inches

**Overall Width:**

1.406 inches

**First Flat Length:**

0.360 inches single actuator

**Flat Height:**

0.210 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.520 inches single actuator

**Individual Section Quantity:**

5

**Operating Temperature Range:**

-55.0 to 71.0 degrees celsius

**Switch Contact Basic Design:**

Coded

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Cam actuated

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

5.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

21 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

17.1 degrees single actuator

**Contact Load Current Rating:**

25.0 milliamperes resistive load dc at sea level

**Contact Arrangement Truth Table:**

Special single section

**Special Truth Table Identification:**

80207-special 1-2-3-4-5 each section

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0