

View Online at <https://aerobasegroup.com/nsn/5930-00-152-8666>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.688 inches

Overall Height:

2.000 inches

Overall Width:

1.375 inches

Unthreaded Mounting Hole Diameter:

0.313 inches

Distance Between Mounting Facility Centers:

1.750 inches

Capillary Tube Length:

21.5 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

25.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+194.00 to 197.00 actuation point degrees fahrenheit and +194.00 to 197.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

277.0 dc at sea level third voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0