

View Online at <https://aerobasegroup.com/nsn/5930-00-152-8666>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.688 inches

**Overall Height:**

2.000 inches

**Overall Width:**

1.375 inches

**Unthreaded Mounting Hole Diameter:**

0.313 inches

**Distance Between Mounting Facility Centers:**

1.750 inches

**Capillary Tube Length:**

21.5 inches

**Tempurature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

25.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+194.00 to 197.00 actuation point degrees fahrenheit and +194.00 to 197.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

277.0 dc at sea level third voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0