

View Online at <https://aerobasegroup.com/nsn/5930-00-153-0120>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Height:

Between 1.235 inches and 1.265 inches

Overall Width:

2.000 inches

Shaft Diameter:

0.247 inches 1st actuator and 0.250 inches 1st actuator

Shaft Length:

0.438 inches 2nd actuator

Individual Section Quantity:

7

Operating Temperature Range:

-65.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

13 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor and dummy terminal

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

13 all actuators

Shaft Type:

Round all actuators

Terminal Type:

Printed circuit

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

25.7 degrees all actuators

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Special Features:

Includes twenty fixed resistors

Precious Material And Location:

Clips and rotor blades and contact surfaces silver and contact surfaces gold

Precious Material:

Silver and gold

Style Designator:

Wafer, printed board, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0