## NSN 5930-00-153-4259

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-153-4259

**Thread Class:** 

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

**Overall Length:** 

3.062 inches

First Flat Length:

0.337 inches single actuator

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

**Shaft Diameter:** 

0.247 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

0.937 inches single actuator

**Overall Diameter:** 

1.047 inches

**Nonturn Device Radius:** 

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:** 

3

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Operating Tempurature Range:** 

-65.0 to 85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

2 each section front

**Throw Quantity:** 

3 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

45.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Round, flatted single actuator

## **NSN 5930-00-153-4259**Rotary Switch - Page 2 of 2

A052b0



Terminal Type:
Tab, solder lug
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load ac at sea level
Style Designator:
Circular wafer, bushing mount
Test Data Document:
31349-mil-s-3786/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fila·