

View Online at <https://aerobasegroup.com/nsn/5930-00-153-4447>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.312 inches 1st mounting facility

Overall Length:

3.439 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.688 inches single actuator

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

1.375 inches 2nd mounting facility

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

21 each section front

Mounting Method:

Bracket 2nd mounting facility and threaded hole 2nd mounting facility

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

21 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section front

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+6.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Terminals and contacts silver

Precious Material:

Silver

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0