# NSN 5930-00-153-4554

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-153-4554

T	hr	ea	d	CI	ass:

2a single mounting facility

#### **Thread Length:**

0.375 inches single mounting facility

**Overall Length:** 

2.344 inches

#### **Overall Height:**

1.000 inches

#### **Overall Width:**

0.937 inches

### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.214 inches single actuator and 0.218 inches single actuator

#### **Shaft Diameter:**

0.247 inches single actuator and 0.250 inches single actuator

# **Shaft Length:**

0.750 inches single actuator

#### **Nonturn Device Radius:**

0.375 inches at 3: 00 o'clock

# **Individual Section Quantity:**

3

#### **Nonturn Device Type:**

Tab at 3: 00 o'clock

# **Operating Tempurature Range:**

-65.0 to 85.0 degrees celsius

# **Switch Contact Basic Design:**

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

# **Throw Quantity:**

3 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# **Shaft Flat/slot Angular Location:**

105.0 degrees from nonturn device single actuator

# **Switch Actuator Indexing Position Quantity:**

3 single actuator

# **NSN 5930-00-153-4554**Rotary Switch - Page 2 of 2

A052b0



Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
120.0 degrees single actuator
Detent Rotational Torque Range:
+12.000 to 96.000 inch-ounces single actuator
Contact Load Current Rating:
1.0 amperes resistive load dc at sea level
Style Designator:
Circular wafer, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: