

View Online at <https://aerobasegroup.com/nsn/5930-00-153-5581>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.297 inches

Body Length:

1.937 inches

Body Width:

0.687 inches

Body Height:

0.953 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.156 inches

Actuator Height:

0.109 inches

Actuator Free Position Height:

1.124 inches

Maximum Voltage Rating In Volts:

480.0 ac

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

15.0 ounces

Actuator Movement:

Between 0.012 pretravel inches and 0.062 overtravel inches and 0.001 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0