NSN 5930-00-153-5581

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:

Dustproof

1.000 inches **Bushing Length:**

0.297 inches

Bushing/hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-153-5581

Center To Center Distance Between Mounting Facilities Parallel To Length:

Body Length:
1.937 inches
Body Width:
0.687 inches
Body Height:
0.953 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.156 inches
Actuator Height:
0.109 inches
Actuator Free Position Height:
1.124 inches
Maximum Voltage Rating In Volts:
480.0 ac
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
6.0 ounces
Switch Actuating Force:
15.0 ounces
Actuator Movement:
Between 0.012 pretravel inches and 0.062 overtravel inches and 0.001 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Terminal Type And Quantity:
3 screw

NSN 5930-00-153-5581

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0