

View Online at <https://aerobasegroup.com/nsn/5930-00-153-5619>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

1.000 inches

Bushing Length:

1.000 inches

Body Length:

1.200 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

Between 1.345 inches and 1.405 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

C5 aircraft

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Thread Series Designator:

Un

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0