NSN 5930-00-153-5619

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-153-5619 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Body Diameter:** 1.000 inches **Bushing Length:** 1.000 inches **Body Length:** 1.200 inches **Actuator Style:** Round **Actuator Diameter:** 0.250 inches **Actuator Height:** 0.375 inches **Actuator Free Position Height:** Between 1.345 inches and 1.405 inches **Maximum Voltage Rating In Volts:** 28.0 dc **End Application:** C5 aircraft **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 4 pole, double throw, one position momentary single switch unit **Switch Release Force:**

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

NSN 5930-00-153-5619

Sensitive Switch - Page 2 of 2



Thread Series Designator:
Un
Terminal Type And Quantity:
12 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0