NSN 5930-00-153-8388

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Thread Class:

Dustproof

12

Overall Length: 7.624 inches Overall Height: 2.812 inches Overall Width: 2.812 inches Shaft Length:

2b single mounting facility

1.312 inches single actuator Individual Section Quantity:



View Online at https://aerobasegroup.com/nsn/5930-00-153-8388

Longest Horizontal Distance Between Mounting Centers: 2.296 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.296 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 5 each section rear **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Rectangular/square, threaded hole single actuator **Square Shaft Size:** 0.250 inches single actuator **Terminal Type:** Tab w/screw

NSN 5930-00-153-8388

Rotary Switch - Page 2 of 2



Conta	ct Sv	vitchin	a Act	ion:
oonta	10L 01	VILCIIII :	I ACL	IVII.

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0