## NSN 5930-00-153-9063

**Hazardous Locations/environmental Protection:** 

**Longest Horizontal Distance Between Mounting Centers:** 

Rotary Switch - Page 1 of 2

**Thread Class:** 

Overall Length: 7.437 inches Overall Height: 2.812 inches Overall Width: 2.812 inches Shaft Length:

Dustproof

12

2b single mounting facility

1.312 inches single actuator Individual Section Quantity:



View Online at https://aerobasegroup.com/nsn/5930-00-153-9063

2.296 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.296 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
3 each section rear
Mounting Method:
Threaded hole single mounting facility
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
125.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw

## NSN 5930-00-153-9063

Rotary Switch - Page 2 of 2



Contact	<b>Switching</b>	Action:
CUIILACL	SWILCIIIII	ACLIOII.

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0