# NSN 5930-00-155-0762

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-155-0762

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

1.754 inches

## **Overall Height:**

1.000 inches

## **Overall Width:**

0.937 inches

## Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

## Shaft Length:

0.875 inches single actuator

## **Nonturn Device Radius:**

## 0.375 inches at 3: 00 o'clock

## Individual Section Quantity:

1

## Nonturn Device Type:

Tab at 3: 00 o'clock

## **Operating Tempurature Range:**

-65.0 to 85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

4 single section rear

## **Throw Quantity:**

2 single section rear

## Mounting Method:

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

12 single actuator

## Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

# NSN 5930-00-155-0762

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Adjustable stop single actuator

## **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

## Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0