

View Online at <https://aerobasegroup.com/nsn/5930-00-155-1025>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.925 inches

**Body Width:**

0.688 inches

**Body Height:**

0.938 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

2.481 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.188 inches

**Housing Height:**

1.859 inches

**Housing Length:**

3.016 inches

**Housing Width:**

1.625 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

0.187 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.437 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 6.0 ounces and 14.0 ounces

**Actuator Movement:**

Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 5.000 amperes inductive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0