

View Online at <https://aerobasegroup.com/nsn/5930-00-156-3315>

**Thread Class:**

3a single pressure connection

**Overall Length:**

2.000 inches

**Pressure Switch Type:**

Absolute

**Width Across Flats:**

0.750 inches

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:**

Inlet connection

**Thread Qty Per Inch (tpi):**

24 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

210.00 pounds per square inch

**Thread Size:**

0.375 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Threaded stud

**Contact Load Current Rating:**

2.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

38.00 actuation point pounds per square inch gage and 6.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Special Features:**

Phosphate (alodine) finish on port cap

**Media For Which Designed:**

Liquid

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0