

View Online at <https://aerobasegroup.com/nsn/5930-00-159-6746>

Thread Class:

3a single pressure connection

Overall Length:

4.750 inches

Outside Diameter:

0.500 inches single connection

Body Length:

3.250 inches

Overall Diameter:

5.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Terminal

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable

Contact Adjustment Range:

+0.15 to 2.00 actuation point inches of water

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

0.05 deactuation point inches of water and 0.10 differential point inches of water

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0