NSN 5930-00-160-2337

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-160-2337

Overall Length:
1.250 inches
Overall Height:
0.440 inches
Overall Width:
0.401 inches
Mounting Slot Width:
0.125 inches
Body Length:
0.776 inches
Body Width:
0.401 inches
Body Height:
0.251 inches
Distance Between Mounting Facility Centers:
1.000 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -85.0 degrees fahrenheit and 300.0 degrees fahrenheit
Mounting Method:
Bracket and slot
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
2.5 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
-20.00/+200.00 actuation point degrees fahrenheit and -20.00 to 200.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

112.00 actuation point degrees fahrenheit and 107.00 deactuation point degrees fahrenheit

NSN 5930-00-160-2337

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts	ontact	Voltage	Rating	In	Volts
---------------------------------	--------	---------	--------	----	-------

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0