

View Online at <https://aerobasegroup.com/nsn/5930-00-160-5452>

Overall Height:

1.750 inches

Overall Width:

0.563 inches

Shaft Diameter:

0.250 inches single actuator

Individual Section Quantity:

1

End Application:

Mforrestal class cv, whidbey island class lsd, spruance class dd (963), nimitz class cvn, cimmaron class ao, supply class aoe, oliver perry class ffg, tarawa class lha, safeguard class ars, virginia class cgn (41)

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Flange single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

33.7 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Special Features:

Lever attached; weapon system essential

Style Designator:

Circular wafer, panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0