NSN 5930-00-161-3178

Thermostatic Switch - Page 1 of 2

480.0 ac at sea level first voltage



View Online at https://aerobasegroup.com/nsn/5930-00-161-3178

Overall Length:
3.500 inches
Overall Height:
4.375 inches
Overall Width:
2.500 inches
Body Height:
3.500 inches
Capillary Tube Length:
72.000 inches
Bulb Length:
3.625 inches
Bulb Diameter:
0.688 inches
Longest Horizontal Distance Between Mounting Centers:
2.750 inches
Longest Vertical Distance Between Mounting Centers:
2.750 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Surface
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
500.0 milliamperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+90.00 to 240.00 actuation point degrees fahrenheit and +55.00 to 235.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:

NSN 5930-00-161-3178

Thermostatic Switch - Page 2 of 2



Frequency In Hertz:
400.0 single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0