NSN 5930-00-161-3966

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-161-3966

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
5.350 inches
Overall Height:
3.080 inches
Overall Width:
3.000 inches
Case Material:
Metal
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.281 inches
Housing Height:
2.600 inches
Housing Length:
4.350 inches
Housing Width:
3.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.450 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.360 inches
Maximum Voltage Rating In Volts:
440.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
32.0 ounces
Switch Actuating Force:

48.0 inch-ounces

NSN 5930-00-161-3966

Sensitive Switch - Page 2 of 2



Actuator	Movement:
----------	-----------

10.0 pretravel degrees and 50.0 overtravel degrees and 1.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 6.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0