

View Online at <https://aerobasegroup.com/nsn/5930-00-161-4255>

Thread Length:

0.375 inches single mounting facility

Overall Height:

1.313 inches

Overall Width:

1.125 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.375 inches 1st actuator

Nonturn Device Radius:

0.531 inches at 9:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 9:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section periphery

Throw Quantity:

6 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest dc voltage rating at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

750.0 milliamperes resistive load ac at sea level

Special Features:

Rear power switch attached

Precious Material And Location:

Contacts and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0