# NSN 5930-00-161-4403

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-161-4403

# **Thread Class:**

2a single mounting facility

# **Thread Length:**

0.375 inches single mounting facility

# **Overall Length:**

3.516 inches

## **Overall Height:**

1.048 inches

## **Overall Width:**

0.952 inches

#### First Flat Length:

0.500 inches single actuator

## Flat Height:

0.198 inches single actuator and 0.202 inches single actuator

#### Shaft Diameter:

0.247 inches single actuator and 0.250 inches single actuator

## Shaft Length:

1.688 inches single actuator

## **Nonturn Device Radius:**

0.375 inches at 3: 00 o'clock

# Individual Section Quantity:

3

#### Nonturn Device Type:

Tab at 3: 00 o'clock

#### **Operating Tempurature Range:**

-65.0 to 85.0 degrees celsius

# Switch Contact Basic Design:

Nonpile-up nonsymmetrical

# **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# Shaft Flat/slot Angular Location:

270.0 degrees from nonturn device single actuator

# Switch Actuator Indexing Position Quantity:

10 single actuator

# Shaft Type:

Round, flatted single actuator

# **Terminal Type:**

Tab, solder lug

# NSN 5930-00-161-4403

Rotary Switch - Page 2 of 2



## Switch Actuator Positioning Increment:

36.0 degrees single actuator

# **Detent Rotational Torque Range:**

+12.000/+64.000 inch-ounces single actuator

# **Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

# Style Designator:

Circular wafer, bushing mount

## **Test Data Document:**

81349-mil-s-3786/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life: N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A052b0