

View Online at <https://aerobasegroup.com/nsn/5930-00-162-1594>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.876 inches

**Body Width:**

0.346 inches

**Body Height:**

0.600 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.078 inches

**Actuator Height:**

0.115 inches

**Actuator Free Position Height:**

0.495 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 5.0 ounces and 19.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 3.300 amperes motor ac

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0