

View Online at <https://aerobasegroup.com/nsn/5930-00-162-8655>

**Thread Class:**

2a single mounting facility

**Overall Length:**

3.200 inches

**Overall Height:**

1.500 inches

**Overall Width:**

0.910 inches

**First Flat Length:**

0.310 inches single actuator

**Flat Height:**

0.093 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Nonturn Device Radius:**

0.250 inches at 6: 00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Pin at 6: 00 o'clock

**Switch Contact Basic Design:**

Pile-up

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Cam actuated

**Pile-up Contact Form Arrangement:**

1c each switch each section in-line

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Solder stud

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level and 3.0 amperes inductive load dc at sea level and 2.4 amperes lamp load dc at sea level and 4.0 amperes motor load dc at sea level

**Special Features:**

Case internally grounded

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0