

View Online at <https://aerobasegroup.com/nsn/5930-00-163-2081>

Hazardous Locations/environmental Protection:

Driptight

Overall Length:

Between 1.164 inches and 1.178 inches

Overall Height:

0.272 inches

Body Diameter:

0.632 inches

Body Height:

0.252 inches

Distance Between Mounting Facility Centers:

Between 0.930 inches and 0.944 inches

Tempurature Sensing Element Type:

Disc

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 450.0 degrees fahrenheit

Mounting Method:

Bracket

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

3.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

212.00 actuation point degrees fahrenheit and 180.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0