

View Online at <https://aerobasegroup.com/nsn/5930-00-163-2546>

Thread Class:

2b all threaded hole

Overall Length:

2.562 inches

Overall Height:

1.750 inches

Overall Width:

1.500 inches

Body Length:

1.656 inches

Distance Between Mounting Facility Centers:

2.187 inches

Capillary Tube Length:

45.000 inches

Bulb Length:

1.375 inches

Bulb Diameter:

0.375 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

8.3 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+9.00/+49.00 actuation point degrees fahrenheit and +9.00 to 49.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point dial and external actuation point dial

Contact Stimulus Rating:

20.00 actuation point degrees fahrenheit and 10.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0