NSN 5930-00-163-5151

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-163-5151

Thread Class:
2b all threaded hole
Overall Height:
3.781 inches
Body Height:
1.781 inches
Distance Between Mounting Facility Centers:
1.750 inches
Capillary Tube Length:
60.0 inches
Bulb Length:
7.500 inches
Bulb Diameter:
0.187 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
Between 140.0 degrees fahrenheit and 530.0 degrees fahrenheit
Mounting Method:
Bracket and threaded hole
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+140.00 to 500.00 actuation point degrees fahrenheit and +140.00/+500.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point dial and external actuation point dial

Contact Voltage Rating In Volts:

240.0 ac at sea level single voltage

NSN 5930-00-163-5151Thermostatic Switch - Page 2 of 2



Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Unc all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0