

View Online at <https://aerobasegroup.com/nsn/5930-00-164-0915>

Body Style:

Hole mounted

Actuator Style:

Roller plunger

Actuator Free Position Height:

3.920 inches

Actuator Roller Diameter:

1.000 inches

Actuator Roller Width:

0.250 inches

Housing Height:

2.160 inches

Housing Length:

5.750 inches

Housing Width:

2.120 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.500 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

18

Thread Size:

0.312 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

96.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.475 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

150.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0