

View Online at <https://aerobasegroup.com/nsn/5930-00-164-0915>

**Body Style:**

Hole mounted

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

3.920 inches

**Actuator Roller Diameter:**

1.000 inches

**Actuator Roller Width:**

0.250 inches

**Housing Height:**

2.160 inches

**Housing Length:**

5.750 inches

**Housing Width:**

2.120 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.500 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

0.312 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

96.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.475 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

150.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0