

View Online at <https://aerobasegroup.com/nsn/5930-00-165-2679>

**Thread Class:**

2a single threaded bushing

**Thread Length:**

0.125 inches single threaded bushing

**Hazardous Locations/environmental Protection:**

Gastight

**Overall Length:**

0.352 inches

**Body Length:**

0.165 inches

**Temperature Sensing Element Type:**

Internal sensor

**Width Across Flats:**

0.280 inches

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

28 single threaded bushing

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

1.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

212.00 actuation point degrees fahrenheit and 228.00 actuation point degrees fahrenheit and 182.00 deactuation point degrees fahrenheit and 198.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Special Features:**

Case grounded

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Plug

**Test Data Document:**

96906-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0