

View Online at <https://aerobasegroup.com/nsn/5930-00-165-2679>

Thread Class:

2a single threaded bushing

Thread Length:

0.125 inches single threaded bushing

Hazardous Locations/environmental Protection:

Gastight

Overall Length:

0.352 inches

Body Length:

0.165 inches

Tempurature Sensing Element Type:

Internal sensor

Width Across Flats:

0.280 inches

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

28 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

212.00 actuation point degrees fahrenheit and 228.00 actuation point degrees fahrenheit and 182.00 deactuation point degrees fahrenheit and 198.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Special Features:

Case grounded

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Plug

Test Data Document:

96906-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0