

View Online at <https://aerobasegroup.com/nsn/5930-00-165-3480>

**Body Style:**

Bushing mount

**Bushing Length:**

0.468 inches

**Body Length:**

0.546 inches

**Body Width:**

0.546 inches

**Body Height:**

0.706 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

1.116 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position no locking action and center position no locking action

**Maximum Voltage Rating In Volts:**

115.0 ac and 50.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0