

View Online at <https://aerobasegroup.com/nsn/5930-00-165-9084>

Thread Class:

3b all pressure connection

Inside Diameter:

0.438 inches second connection

Thread Length:

0.562 inches all threaded stud

Overall Length:

2.873 inches

Body Length:

1.998 inches

Overall Diameter:

2.500 inches

Pressure Switch Type:

Differential

Mounting Facility Circle Radius:

0.750 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 168.0 degrees fahrenheit

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Proof Pressure:

41.00 inches of water

Thread Size:

0.438 inches second pressure connection

Mounting Facility Pattern:

Four position circular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

68.00 inches of water

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.5 amperes lamp load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

13.00 actuation point inches of water and 11.00 deactuation point inches of water

Contact Voltage Rating In Volts:

5.0 dc at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded internal all connections

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0