NSN 5930-00-166-2016

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-166-2016

Body S	tyle:
Bushing	mount
Hazard	ous Locations/environmental Protection:
Weathe	rproof
Bushin	g Length:
Between	n 0.450 inches and 0.490 inches
Body L	ength:
1.346 in	ches
Body W	lidth:
1.025 in	ches
Actuato	or Style:
Round	
Actuato	or Diameter:
0.240 in	ches
Actuato	or Height:
Between	n 0.660 inches and 0.720 inches
Actuato	or Position-action Relationship:
Up posi	tion maintained and down position maintained
Maximu	ım Voltage Rating In Volts:
220.0 a	c and 250.0 dc
Inclosu	ге Туре:
Fully en	closed
Mountii	ng Method:
Threade	ed bushing
Feature	s Provided:
Actuato	rseal
Thread	y Qty Per Inch (tpi):
32	
Thread	Size:
0.469 in	ches
Nonpile	-up Contact Arrangement:
2 pole,	single throw, both positions maintained single switch unit
Critical	ity Code Justification:
Feat	
Contac	t Load Current Rating At Maximum Rated Voltage:
500.000	milliamperes resistive dc and 9.000 amperes resistive ac
Special	Features:
Item mu	st comply with rqmt of desc production standard no. L00165
Thread	Series Designator:
Uns	
Termina	al Type And Quantity:

4 tab w/screw

NSN 5930-00-166-2016

Toggle Switch - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0