

View Online at <https://aerobasegroup.com/nsn/5930-00-166-2193>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

Between 0.450 inches and 0.490 inches

Body Length:

1.457 inches

Body Width:

0.641 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

Between 0.660 inches and 0.720 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

220.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

Special Features:

Item must comply with rqmt of desc production standard no. L00416

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0