# NSN 5930-00-166-9944

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-166-9944

# **Thread Class:**

2a single mounting facility

### Thread Length:

0.380 inches single mounting facility

# **Overall Length:**

2.380 inches

#### **Overall Height:**

1.500 inches

#### **Overall Width:**

1.310 inches

#### Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

#### Shaft Length:

0.880 inches single actuator

#### **Nonturn Device Radius:**

# 0.440 inches at 9:00 o'clock

# Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 9: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

#### **Throw Quantity:**

7 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

# **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

15.0 dc at sea level

# **Rotor Through Connection Quantity:**

1 each section

# Switch Actuator Indexing Position Quantity:

12 single actuator

# Shaft Type:

Round single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-166-9944

Rotary Switch - Page 2 of 2



# Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Adjustable stop single actuator

# **Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A052b0