NSN 5930-00-167-1731

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-167-1731

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| Between 1.922 inches and 1.954 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 0.907 inches and 0.927 inches |
| Overall Width: |
| Between 0.672 inches and 0.704 inches |
| Body Length: |
| Between 1.922 inches and 1.954 inches |
| Body Width: |
| Between 0.672 inches and 0.704 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.139 inches and 0.142 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| Between 0.484 inches and 0.516 inches |
| Actuator Free Position Height: |
| Between 1.407 inches and 1.531 inches |
| Maximum Voltage Rating In Volts: |
| 125.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained single switch unit |
| Switch Release Force: |
| 0.5 ounces |
| Switch Actuating Force: |
| 16.0 ounces |
| Actuator Movement: |
| 0.156 overtravel inches and 0.005 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 15.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5930-00-167-1731

Sensitive Switch - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A053a0