

View Online at <https://aerobasegroup.com/nsn/5930-00-167-1746>

Body Style:

Hole mounted

Overall Length:

1.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Overall Width:

0.688 inches

Body Length:

Between 1.922 inches and 1.954 inches

Body Width:

Between 0.672 inches and 0.704 inches

Body Height:

Between 0.953 inches and 0.985 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.187 inches and 0.219 inches

Actuator Free Position Height:

Between 1.089 inches and 1.129 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

26.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.062 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 6.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes motor ac

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0