

View Online at <https://aerobasegroup.com/nsn/5930-00-167-1746>

**Body Style:**

Hole mounted

**Overall Length:**

1.938 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Overall Width:**

0.688 inches

**Body Length:**

Between 1.922 inches and 1.954 inches

**Body Width:**

Between 0.672 inches and 0.704 inches

**Body Height:**

Between 0.953 inches and 0.985 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.187 inches and 0.219 inches

**Actuator Free Position Height:**

Between 1.089 inches and 1.129 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, double break/double make, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

26.0 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.062 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 6.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes motor ac

**Terminal Type And Quantity:**

5 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0