

View Online at <https://aerobasegroup.com/nsn/5930-00-167-1767>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.310 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

0.844 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.158 inches

Actuator Height:

0.366 inches

Actuator Free Position Height:

1.160 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

28.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.062 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0