NSN 5930-00-167-2167

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-167-2167

Body Style:

Hole mounted

Overall Length:

1.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.520 inches

Overall Width:

0.822 inches

Body Length:

1.253 inches

Body Width:

0.515 inches

Body Height:

0.505 inches

Unthreaded Mounting Hole Diameter:

0.101 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.312 inches

Actuator Length:

0.250 inches

Actuator Style:

Rectangular

Actuator Height:

0.093 inches

Actuator Width:

0.296 inches

Actuator Adapter Style:

Nonadjustable arm

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

20.0 ounces

Actuator Movement:

0.027 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc and 6.000 amperes motor dc and 10.000 amperes resistive ac and 10.000

amperes inductive ac and 6.000 amperes motor ac

NSN 5930-00-167-2167

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

2 tab, solder lug and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0