NSN 5930-00-167-2167

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-167-2167

Body Style: Hole mounted Overall Length: 1.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.520 inches Overall Width: 0.822 inches Body Length: 1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches Actuator Style:
Overall Length: 1.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.520 inches Overall Width: 0.822 inches Body Length: 1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
1.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.520 inches Overall Width: 0.822 inches Body Length: 1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length: 0.520 inches Overall Width: 0.822 inches Body Length: 1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
Overall Width: 0.822 inches Body Length: 1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
Overall Width: 0.822 inches Body Length: 1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
0.822 inches Body Length: 1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
Body Length: 1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
1.253 inches Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
Body Width: 0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
0.515 inches Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
Body Height: 0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
0.505 inches Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
Unthreaded Mounting Hole Diameter: 0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
0.101 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Height: 0.312 inches Actuator Length: 0.250 inches
0.312 inches Actuator Length: 0.250 inches
Actuator Length: 0.250 inches
0.250 inches
Actuator ctyle.
Rectangular
Actuator Height:
0.093 inches
Actuator Width:
0.296 inches
Actuator Adapter Style:
Nonadjustable arm
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
20.0 ounces
Actuator Movement:

Contact Load Current Rating At Maximum Rated Voltage:

0.027 differential inches

10.000 amperes resistive dc and 10.000 amperes inductive dc and 6.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes motor ac

NSN 5930-00-167-2167

Sensitive Switch - Page 2 of 2



Terminal Type And Quanti	ty	:
--------------------------	----	---

2 tab, solder lug and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0