NSN 5930-00-167-3598

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-167-3598

| D 1 0/1 |
|---|
| Body Style: |
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 1.265 inches |
| Overall Width: |
| 0.270 inches |
| Bushing Length: |
| 0.350 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.270 inches |
| Body Height: |
| 0.350 inches |
| Case Material: |
| Plastic |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.115 inches |
| Actuator Height: |
| 0.410 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Maximum Voltage Rating In Volts: |
| 20.0 ac and 20.0 dc |
| Mounting Surface To Terminal End Distance: |
| 0.505 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |

Honpile up Contact Arrangement.

1 pole, double throw, both positions maintained single switch unit

NSN 5930-00-167-3598

Toggle Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 400.000 milliamperes resistive ac

Precious Material And Location:

Contacts and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0