

View Online at <https://aerobasegroup.com/nsn/5930-00-167-4022>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.450 inches

Overall Height:

1.932 inches

Overall Width:

0.500 inches

Bushing Length:

0.312 inches

Body Length:

0.450 inches

Body Width:

0.500 inches

Body Height:

0.410 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.214 inches

Actuator Height:

Between 0.580 inches and 0.650 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Maximum Voltage Rating In Volts:

20.0 ac and 20.0 dc

Mounting Surface To Terminal End Distance:

0.505 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 400.000 milliamperes resistive ac

Precious Material And Location:

Contacts and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0