NSN 5930-00-167-8030

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-167-8030

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 1.563 inches **Overall Height:** 1.093 inches **Overall Width:** 0.952 inches **Shaft Diameter:** 0.125 inches single actuator **Shaft Length:** 0.688 inches single actuator **Nonturn Device Radius:** 0.375 inches at 3: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 3 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

NSN 5930-00-167-8030

Rotary Switch - Page 2 of 2



| Switch Actuator Stop Device Type: |
|--|
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 1.5 amperes resistive load dc at sea level |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Circular wafer, bushing mount |
| Thread Series Designator: |
| Unef single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A052b0