

View Online at <https://aerobasegroup.com/nsn/5930-00-167-8050>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

Between 0.552 inches and 0.572 inches

Body Length:

Between 0.888 inches and 0.920 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

Between 0.370 inches and 0.377 inches

Actuator Height:

Between 0.240 inches and 0.260 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action, with contact on arm. Single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0