## NSN 5930-00-168-7964

Push Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-168-7964

| Body Style:   |
|---|
| Panel mount   |
| Overall Length:   |
| 0.870 inches  |
| Overall Height:   |
| 3.050 inches  |
| Overall Width:  |
| 0.870 inches  |
| Body Length:  |
| 0.750 inches  |
| Body Width:   |
| 0.750 inches  |
| Actuator Length:  |
| 0.680 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.300 inches  |
| Actuator Width:   |
| 0.680 inches  |
| Actuator Color:   |
| Black single actuator and black single actuator and black single actuator   |
| Illuminated Actuator Color:   |
| Red single actuator and green single actuator and yellow single actuator  |
| Actuator Inscription:   |
| 5/5/5 single actuator   |
| Illuminated Actuator Color Sequence:  |
| Upper left half of actuator red upper right half of actuator yellow lower half of actuator green                            |
| Maximum Voltage Rating In Volts:  |
| 115.0 ac and 28.0 dc  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Nonpile-up Contact Arrangement:   |
| 4 pole, double throw, two positions momentary single switch unit  |
| Contact Load Current Rating At Maximum Rated Voltage:   |
| 2.000 amperes resistive dc and 750.000 milliamperes lamp dc and 1.500 amperes resistive ac and 250.000 milliamperes lamp ac |
| Terminal Type And Quantity:   |
| 17 tab, solder lug  |
| Shalf Life:   |

## NSN 5930-00-168-7964

Push Switch - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A053a0