## NSN 5930-00-168-7998

Pressure Switch - Page 1 of 2

0.550 inches single pressure connection

**Thread Class:** 

**Thread Length:** 

3a single pressure connection



View Online at https://aerobasegroup.com/nsn/5930-00-168-7998

**Hazardous Locations/environmental Protection:** Explosion proof **Overall Length:** 2.800 inches **Overall Height:** 0.680 inches **Body Diameter:** 0.719 inches **Body Length:** 2.250 inches **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -85.0 degrees fahrenheit and 275.0 degrees fahrenheit **Mounting Method:** Input port Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Proof Pressure:** 4500.00 pounds per square inch **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Sensing Element Burst Pressure:** 7500.00 pounds per square inch **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 3.0 amperes resistive load single voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 50.00 differential point degrees fahrenheit **Contact Voltage Rating In Volts:** 

28.0 dc at sea level single voltage

## NSN 5930-00-168-7998

Pressure Switch - Page 2 of 2

Fiig: A048b0



Pressure Connector Type:
External seat-gasket seal, threaded external single connection
Media For Which Designed:
Gas
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Thread Series Designator:
Un single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No