

View Online at <https://aerobasegroup.com/nsn/5930-00-168-8015>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.218 inches single mounting facility

**Width Between Flats:**

0.064 inches single actuator

**Overall Length:**

1.976 inches

**First Flat Length:**

0.093 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.328 inches single actuator

**Overall Diameter:**

0.720 inches

**Individual Section Quantity:**

5

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

10 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level

**Special Features:**

Weapons system essential

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0